

AC144 Series

Low Cost Miniature Industrial Multipurpose Accelerometer, Side Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±15%




Product Features

Low-Cost mini-MIL Industrial Accelerometer, Great for Hard-to-Reach Locations

- ▶ ± 80 g, Dynamic Range
- ▶ 100 mV/g Frequency Response
- ▶ 2 pin Mini-MIL Side Connector

AC144-1D 2 Pin Mini Mil Connector


Connector	Polarity
Pin	
A	(+)Signal/Power
B	(-)Common



Stock Product

AC144-2D CB110 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC144-3D CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC144-6D CB611 Heavy Duty Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC144-6N CB111 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC144	M/AC144	Environmental		
Sensitivity (±15%)	100 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	36-600,000 CPM	0,6-100,000	Maximum Shock Protection	5,000 g, peak	
Dynamic Range	± 80 g, peak *Vsource ≥ 22V, 12Vbias		Electromagnetic Sensitivity	CE	
Electrical			Sealing	Welded, Hermetic	
Settling Time	<2.5 seconds		Submersible Depth	200 ft.	60 m
Voltage Source (IEPE)	18-30 VDC		SIL Rating	SIL 2	
Constant Current Excitation	2-10 mA		Physical		
Spectral Noise @ 10 Hz	30 µg/√Hz		Sensing Element	PZT Ceramic	
Spectral Noise @ 100 Hz	4 µg/√Hz		Sensing Structure	Shear Mode	
Spectral Noise @ 1000 Hz	2 µg/√Hz		Weight	2.1 oz	60 grams
Output Impedance	<100 ohm		Case Material	316L Stainless Steel	
Bias Output Voltage	7-14 VDC		Connector (Non-Integral)	2 Pin mini-MIL (J Series)	
Case Isolation	>10 ⁸ ohm		Resonant Frequency	1,920,000 CPM	26000 Hz
			Mounting Torque	2 to 5 ft.	2,7 to 6,8