



VAISALA

Order form
Orderer _____

Valid from
December 2013 _____

DPT145 Multiparameter transmitter for SF6 gas

		1	2	3	4	5	6	7	8	9	10	11	
Vaisala Multiparameter Transmitter		DPT145	A			A	A					A	PRICE
1	Probe	DPT145 base - probe with UNF 7/8- 14 thread											
2	Measurement parameters	Td/f, Td/f atm, ppm, P, Pnorm, density and T for SF6 gas											
		Td/f, Td/f atm, ppm, P, Pnorm, density and T for mixed SF6/N2 gas, %SF6 _____ %N2 _____											
3	Digital output	RS-485											
		RS-485 with Modbus RTU mode by default											
4,5	Reserved codes												
6	Output units	Metric units (Celsius, bara)											
		Non-metric units (Fahrenheit, psia)											
7	Mechanical connection	<i>DILO DN8 connector</i>											
		<i>DILO DN20 connector</i>											
		<i>ABB connector</i>											
		<i>Alstom connector</i>											
8	Cable for RS485 output and power supply	None											
		<i>1,5 m Shielded PUR cable with 90°connector</i>											
		<i>3 m Shielded PUR cable with 90°connector</i>											
		<i>5 m Shielded PUR cable with 90°connector</i>											
		<i>10 m Shielded PUR cable with 90°connector</i>											
		<i>3 m Shielded FEP cable with straight connector (Compatible w. combination of Alstom connector + Rain shield)</i>											
		<i>15 m Shielded PUR cable with straight connector</i>											
		<i>20 m Shielded PUR cable with straight connector</i>											
9	Installation accessories	None											
		<i>Weather shield</i>											
10	Special features	None											
11	User' s guide	None											
		Multilingual quick guide											
												Total	
												Total value	

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Example of order code with typical settings:

DPT145 **A** **1** **A** **A** **A** **A** **1** **B** **1** **1** **A** **X**

End customer: _____

Accessories and spare parts

219980	Connection cable for DM70
219690	USB Serial Interface Cable
218675SP	Protection plug for connector
231519SP	1.5 m Shielded PUR cable with 90° connector
231520SP	3 m Shielded PUR cable with 90° connector
231521SP	5 m Shielded PUR cable with 90° connector
231522SP	10 m Shielded PUR cable with 90° connector
226902SP	3 m Shielded FEP cable with straight connector
236407SP	15 m Shielded PUR cable with straight connector
235859SP	20 m Shielded PUR cable with straight connector
ASM210326SP	Weather shield