

Valid from March 2020
Order no.

Restricted

VAISALA

Order form
Purchaser

Valid from March 2020
Order no.

HMT130 Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14
Vaisala HUMICAP® Temperature Transmitter		HMT130	T					A	0						Price
Output parameters	Temperature output only		T												
Transmitter type	Wall mount/fixed probe		A												
	Remote probe with 3 m cable		B												
	Remote probe with 5 m cable		C												
	Remote probe with 10 m cable		D												
	Remote probe with 10 m cable + 10 m extension		E												
	Remote probe with 20 m cable		F												
	Remote probe with 1.2 m cable		G												
Display	No display		0												
	Display		1												
	No Display, no logo		N												
Analog output signal (RS485 also included)	0...1 V 3-wire		B												
	0...5 V 3-wire		C												
	0...10 V 3-wire		D												
SPECIAL	Define scale: 3-wire V *)		X												
Parameter for Output 1	T	-40...+60 °C (-40...+140 °F)	B												
		-20...+80 °C (-4...+176 °F)	C												
		0...+60 °C (+32...+140 °F)	D												
		-40...+80 °C (-40...+176 °F)	E												
		0...+50 °C (+32...+122 °F)	F												
SPECIAL	Define quantity	Scale	X												
Parameter for Output 2	None		A												
			0												
Display Units	Metric		1												
	Non metric		2												
Sensor protection	Plastic grid		1												
	Plastic grid with PTFE filter		2												
	Stainless steel sintered filter (for remote probes only)		3												
	Teflon sintered filter for HMP110 DRW244938SP		E												
Transmitter installation	No accessories		A												
	Rain shield with installation kit (215109)		C												
Installation kit for probe	No accessories		1												
	Duct installation kit (215619)		2												
	Probe mounting flange (226061)		3												
	Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)		5												
	Probe mounting clamp, 1 piece (225501)		6												
Cable bushings	Cable gland for 2...6 mm diameter cable		A												
	Conduit fitting PG9		B												
	Conduit fitting NPT 1/2"		C												
	No bushing (rubber plug)		D												
	All bushings (includes A, B, C and D)		Z												
PC Accessories	No		0												
	Service cable for PC, USB (219685)		1												
Operation manual	No manual		A												
	Multilingual		Z												
															Total
															QTY
															Total value

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130	T	A	1	D	B	A	0	1	A	1	1	A	0	Z
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---