



VAISALA

INDIGO80 Handheld Indicator



INDIGO80 Order Form G010005EN-B Valid from May 2023

Example of order code with typical settings: 1 2 3 4 5 6 7 8 INDIGO80 A 7 N 0 A 1 N 0

Handheld Indicator		SPARE CODE	INDIG080		4
1 Power Supply Unit	USB Cable, no PSU			A	
	Rechargeable with Euro AC-adapter			в	
	Rechargeable with UK AC-adapter			с	
	Rechargeable with US AC-adapter			D	
	Rechargeable with AUS AC-adapter			E	
2 Indicator Accessories	No Accessories			0	
	 Magnetic hanger for Indigo80 handheld indicator 	ASM214318SP		1	
3 Connection Cables for Transmitters	No Connection Cables for Transmitters			N	
	M12-M8 Service Cable	262195SP		A	
4 Connection Cables for Probes	No Connection Cables for Probes			c	,
	M12-M12 Probe Connection Cable	272075SP		1	1
	Flat Cable	CBL210493SP		2	?
5 Carrying Case	No Carrying Case				N
	Weatherproof Carrying Case	ASM214759			A
6 Indicator color	Housing option color grey				
	Housing option color black				
7 Other Options	No Other Options				
	Japanese SW Version				

Selections in bold are included in the prices of the basic versions. NOTE: Selections in italic are available at an extra price

	User Guides
LINKS:	Datasheet
	Vaisala.com product page

Related Items USB Service Cable M12-5F, RS-485 Cable, Spare Part M12/5(M)-M12/5(F), 5x0.34mm2, 1.5m, PP/PUR, BLK Magnetic Hanger Spare Part Indiga80 Case Packaging Flat Cable, M12-5(M) - M12-5(F), 1m Probe Connection Cable (M12-M12), 10 m

Part number 242659 272075SP ASM214318SP ASM214759 CBL210493SP INDIGOCABLE10M

VAISALA

INDIGO80 Order Form G010005EN-B Valid from May 2023

HMP80

Handheld Humidity Probe

		1			1234	ļ	Ę
Handheld Humidity Probe			SPARE CODE	HMP80	1	1	-
1 Probeset		Probe (106 mm) with HUMICAP R2C Sensor ¹			N		
		Long probe (319 mm) with HUMICAP R2C Sensor ²			L		
2 Probe connection cables		No Cable			0		
	•	M12-M12 Probe Connection Cable	272075SP		1	1	
	•	Flat probe connection cable			2	1	
3 Filter		Sintered Stainless Steel Filter ²	HM47280SP				
		Plastic PPS Grid Filter ²	DRW010276SP		в	1	
		PPS Grid With SS Netting ²	DRW010281SP		с		
		Slotted MIM Fliter with Membrane ¹	DRW255306SP		D	1	
		Slotted MIM Fliter with Membrane ¹	ASM214606SP		E		

NOTE:	Selections in bold are included in the prices of the basic versions Selections in italic are available at an extra price. 			
	User Guides		Example of order	code with typical settings:
LINKS:	Datasheet Vaisala.com product page		HMP80	1 2 3 4 5 6 N 7 E 1 S 0
Related Items		Part number		
Cable, Spare Part M12/5(M)-	M12/5(F), 5x0.34mm2, 1.5m, PP/PUR, BLK	272075SP		
Slotted MIM Filter with Mem	brane Spare Part	ASM214606SP		

Cable, Spare Part M12/5(M)-M12/5(F), Sx0.34mm2, 1.5m, PP/PUR, BLK Slotted MIM Filter with Membrane Spare Part Flat Cable, M12-5(M) - M12-5(F), Im PPS Plastic Grid Filter Metal Coated PPS Grid Filter with Stainless Steel Mesh, Female Thread Slotted MIN Filter Spare Part Sintered Stainless Steel Filter, Female Thread Indigo-compatible USB Adapter Part number 272075SP ASM214606SP CBL210493SP DRW010276SP DRW010276SP DRW255306SP HM47280SP USB2

VAISALA

DMP80

Handheld Dew Point Probe

					1	2 3	4	5 (6 7	78
[Handheld Dew Point Probe		SPARE CODE	DMP80			Α	1	AS	S 0
er.e	1 Probeset		Probe with Range [-50+60°C Td], DRYCAP*1805 Sensor		A					
×0			Probe with Range [-70 +30°C Td], DRYCAP9180M sensor		В					
Jard	2 Thread		Mechanical connection, ISO G1/2" thread			G				
-			Mechanical connection, NPT 1/2" thread			N				
	3 Probe connection cables		No Cable			_ c				
		•	M12-M12 Probe Connection Cable			1				
~		•	Flat probe connection cable			2	>			
ssory	5 Accessories for ISO G1/2" thread		Accessories for ISO G1/2" thread option					0		
Ce		•	Sampling Cell with Quick Connector and Leak Screw (DSC74)					1		
ac		•	Sampling Cell with Female Connectors, Inlet G3/8", Outlet G1/4" ISO					2		
		•	Sampling Cell with Swagelok Connectors for 1/4" Tubing (DMT242SC2)					3		
		•	Two-Pressure Sampling Cell (DSC74B)					4		
		•	Two-Pressure Sampling Cell with Coil (DSC74C)					5		

Ą

NOTE:	 Selections in bold are included in the prices of the basic versions. Selections in italic are available at an extra price. 	_	
	User Guides	-	Example of order code with typical settings:
LINKS:	Datasheet Vaisala.com product page		1 2 3 4 5 6 7 8 DMP80 B G 7 A O A S G

Cable, Spare Part M12/5(M)-M12/5(F), 5x0.34mm2, 1.5m, PP/PUR, BLK Flat Cable, M12-5(M) - M12-5(F), Im Sampling Cell DMT242SC with Female Connectors, inlet G3/8" & outlet G1/4" ISO Sampling Cell DMT242SC2 with Swagelok Connectors for 1/4" Tubing Sampling Cell with Quick Connector and Leak Screw Two Pressure Sampling Cell Two Pressure Sampling Cell with Coil Sintered Stainless Steel Filter, Female Thread Indigo-compatible USB Adapter

CBL210493SP CBL210493SF DMT242SC DMT242SC2 DSC74 DSC74B DSC74C HM47280SP USB2

Restricted

INDIGO80 Order Form G010005EN-B Valid from May 2023





	GMP252 CO2 Probe for ppr	n Measurements			INDIGO80 Order Form G010005EN-B Valid from May 2023
1	CO2 Probe for ppm Measu	rements	SPARE CODE	GMP252	1 2 3 4 5 6 7 8 6 1 C 0 B H 3
sory	6 Cable	No Cable			0
cess		M12-M12 Probe Connection Cable (I	ndigo80)		8
ac		Flat Probe Connection Cable (Indig	080)		9

NOTE:	Selections in bold are included in the prices of the basic v • Selections in italic are available at an extra price.	ersions.		
LINKS:	User Guides Datasheet		Example of order of	code with typical settings: 1 2 3 4 5 6 7 8
	Vaisala.com product page		GMP252	6 1 C 0 B 8 H 3
Related Items		Part number		
USB Service Cable M12-5F, RS	S-485	242659		
Probe Mounting Clips (2 pcs)		243257SP		
Probe Mounting Flange		243261SP		
Connection Cable, M12-5F 90	° - Open Wires, 0.6 m	244669SP		
Mounting flange for GMP251 a	and GMP252	252346SP		
Cable, Spare Part M12/5(F)-O	pen, 5x0.34mm2, 1.5m, PP-EPDM/PP, GRY	254294SP		
Cable, Instrumentation, SH, M	12/5(F) RA-Open, 5x0.34mm2, 1.5m, PP/PUR, HF, BLK	255102		
Connection Cable, M12-5F - O	pen Wires, 3 m	26719SP		
Flow Through Adapter Assem	nbly GMP252 Spare Part	ASM212011SP		
Spray Shield (IPX9 Rating)		ASM212017SP		
Flat Cable, M12-5(M) - M12-5(F), 1m	CBL210493SP		
Porous Sintered PTFE Filter, E	Extra Protection	DRW244221SP		
Calibration Adapter		DRW244827SP		
Radiation Shield for Outdoor	Use	DTR250		
Radiation Shield with Mast Ins	stallation Kit	DTR250A		
Indigo-compatible USB Adap	ter	USB2		
Connection Cable, M12-5F - O	pen Wires, 10 m	216546SP		
Connection Cable, M12-5F - C	pen Wires, 1.5 m	223263SP		