

MCB211 Series

High Frequency, Lightweight, Cost Effective Molded Sensor, Top Exit
Molded Integral Cable, 10-32 Mounting, 10 mV/g, ±10%




Product Features

- ▶ Nylon Overmolded Accelerometer
- ▶ IP68 Rated
- ▶ High Frequency, 30 kHz Response

MCB211

CB127 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	MCB211	MCB221	<u>Environmental</u>		
Sensitivity (±10%)	10 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	30-1,800,000 CPM	0.5 Hz-30 kHz	Maximum Shock Protection	10,000 g, peak	
Frequency Response (±10%)	60-900,000 CPM	1 Hz-15 kHz	Electromagnetic Sensitivity	CE Approved	
Frequency Response (±5%)	120-600,000 CPM	2 Hz-10 kHz	Sealing	IP68	
Dynamic Range	± 500 g, peak		SIL Rating	SIL 2	
	*Vsource ≥ 22V, 12Vbias		<u>Physical</u>		
<u>Electrical</u>			Sensing Element	PZT Ceramic	
Settling Time	< 2 Seconds		Sensing Structure	Shear Mode	
Voltage Source (IEPE)	18-30 VDC		Weight	0.35 oz	10 grams
Constant Current Excitation	2-10 mA		Mounting Base	316L Stainless Steel	
Spectral Noise @ 10 Hz	100 µg/√Hz		Mounting Thread	10-32 UNF	
Spectral Noise @ 100 Hz	19 µg/√Hz		Cable Jacket Diameter	0.14 in (3.6 mm)	
Spectral Noise @ 1000 Hz	5 µg/√Hz		Cable Jacket Material	Polyurethane	
Output Impedance	< 100 ohm		Cable Conductor	26 AWG Twisted Shielded Pair	
Bias Output Voltage	10-14 VDC		Resonant Frequency	2,640,000 CPM	44 kHz
Case Isolation	>10 ⁸ ohm		Mounting Torque	1.5 - 2.5 ft. lbs	2.0 to 3.4 Nm