



## QE95LP-S-MB-QED-D0

Pyroelectric detector for laser energy measurement up to 250 J.



### PRODUCT FAMILY KEY FEATURES

#### MODULAR CONCEPT

Increase the power capability of your detector: 2 different cooling modules

#### EXTRA LARGE APERTURE

Effective aperture of 95 mm  $\varnothing$

#### QED ATTENUATOR AVAILABLE

Measure up to 5X higher energies. Available with optional calibration, all wavelengths between 532 & 1064 nm, or single wavelength. [Read more.](#)

#### LOW NOISE LEVEL

15  $\mu$ J for the MB coating

#### TEST TARGET INCLUDED

With the MB models

#### SMART INTERFACE

Containing all the calibration data

#### COMPATIBLE STAND

[STAND-D-233](#)

## SPECIFICATIONS

### MEASUREMENT CAPABILITIES

Spectral range <sup>1</sup>	0.3 - 2.1 $\mu$ m
Typical rise time	2 ms
Repeatability	<0.5%
Maximum repetition frequency	40 Hz
Maximum measurable energy <sup>2</sup>	250 J
Noise equivalent energy <sup>3</sup>	30 $\mu$ J
Maximum pulse width	1.5 ms
Energy calibration uncertainty	$\pm$ 3 %

1. For the calibrated spectral range, see the user manual.
2. At 1064 nm, 150  $\mu$ s, single-shot. Increasing pulse width increases maximum measurable energy.
3. Nominal value. Actual value depends on electrical noise in the measurement system.

### DAMAGE THRESHOLDS

Maximum average power density <sup>1</sup>	600 W/cm <sup>2</sup>
Maximum energy density <sup>2</sup>	8 J/cm <sup>2</sup>
Maximum power	45 W

1. May vary with wavelength and average power.
2. At 1064 nm, 7 ns, 10 Hz. May vary with wavelength and pulse width.

### PHYSICAL CHARACTERISTICS

Cooling	Convection
Aperture diameter	90 mm
Absorber	QED
Dimensions	125H x 127W x 25D mm
Weight	0.78 kg

### ORDERING INFORMATION

QE95LP-S-MB-QED-D0	202194
QE95LP-S-MB-QED-IDR-D0	203311



Specifications are subject to change without notice. Refer to the user manual for complete specifications.

## INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at [gentec-eo.com/contact-us](http://gentec-eo.com/contact-us)