

## SM-10T Densitometer

Measuring Aperture	2mm
Measuring Range	0.00 to 5.00 D
Accuracy	± 0.02 D
Repeatability	± 0.01 D
Preview Stage	2.5"x4"
Warm-up time	None
Film Measuring Depth	7.25" (18.42cm)
Portable Power Source	(2) 9V Alkaline batteries Included
Desktop Power	9V AC Power Supply
Dimensions	4.5"H (11.4cm) 4.5"W( 11.4cm)
	11"L (28.0cm)
Optional	RS-232 Serial Output (CAT# 5008)

SM-10TCAT# 5009

> SM-10TCI CAT.# 5008 \$1,695

ESECO - S& <sup>®</sup> is a manufacturer of photographic, graphic arts, and X-ray equipment. Our products are made and serviced in the USA and backed by over forty vears of technical experience. All ESECO products come with a one year No Hassle warranty.

The S **SM-10T** densitometer assures instant, accurate, and repeatable results that rival the same high standards of more expensive units. Featuring total accuracy of+/- .02 from 0.00 to 5.00 Optical Density and compliant with ANSI / ISO Standard - 5/2.

Low power consuming components and extended battery life features are provided in the automatic "stand-by" mode. For added convenience, it may be operated with the UL/CSA-approved plug-in a/c power adapter furnished with the ? <sup>®</sup> SM-10T. The SM-10TCI is available with a serial interface (CAT# 5008). Use the the SM-10TCI model with the ESECO S <sup>®</sup> QC PAL Software for maximum quality assurance.

> NBS Standard 1009 - Reference Material ID 057901 ANSI / ISO Standard - 5/2