



Instrument Expert Original factory packaging www.dorgean.com



Acclima Solar DataSnap<sup>™</sup>

Solar-powered SDI-12 Data Logger with free Windows<sup>®</sup> PC data logging software

The Acclima Solar DataSnap<sup>™</sup> is a simple-to-use standalone SDI-12 universal data logger with powerful features. It has a rugged, weather resistant, polycarbonate enclosure (NEMA 4) with a solar panel circuit that charges a lithium ion 18650 battery ensuring continuously reliable, long-term data logging. It is designed to work with Acclima's world renowned soil water content TDR and TDT SDI-12 sensors. It will also work with a wide range of third-party SDI-12 sensors. The Solar DataSnap<sup>™</sup> will automatically detect and configure Acclima sensors with the click of a button in its free, downloadable Windows<sup>®</sup> software known as SnapView<sup>™</sup>. This software allows a user to easily configure reading intervals for up to 10 SDI-12 sensors. It will also work with a wide range of third-party SDI-12 sensors. It supports up to five data points per sensor (using the SDI-12 M! command). The software can synchronize data from multiple DataSnaps down to a Windows<sup>®</sup> PC through a USB connection with the Solar DataSnap. Data is easily exported for use in the form of CSV files which are are automatically generated and downloaded to a micro-USB thumb drive.

## Features:

- -Accomodates up to 10 SDI-12 sensors
- -Requires no SDI-12 programming knowledge
- -Includes SnapView for Windows<sup>®</sup> PCs
- -USB to SDI-12 bridge
- -Short circuit protection
- -Data logging of the first 5 datapoints with SDI-12 M! command
- -Lithium ion 18650 battery recharges with solar power
- -Long-lasting rechargable battery (3500 mAh, 3.7v)
- -Battery power monitoring feature from SnapView
- -Battery power low warning flash on power-up
- (green LED then red LED) -Total memory capacity supports over 59,000
- scans with each scan storing up to 5 datapoints -SDI-12 sensor compatibility
- -Compatible with terminal software applications like HyperTerminal or PuTTy
- -NEMA 4 rated weather-UV resistant enclosure
- -Operating temperature range: -20°C to +50°C -1.25 lbs. 6.5"x 6.5"x 3.7" without conduit



Model No. ACC-AGR-D02S

Acclima, Inc., 1763 W. Marcon Lane, Ste. 175 Meridian, Idaho 83642 U.S.A. Toll Free: (866) 887-1470 Fax: (208) 887-6368 www.acclima.com Inquiries: sales@acclima.com