

TA234 Series

Dual Output Sensor, Temperature & Acceleration, Side Exit 3 Pin Connector, 500 mV/g, 10 mV/°C, ±10%




Product Features

- High Performance in a Low Cost Sensor
- Helps to Detect Bearing Defects and Temperature Changes
- ▶ Temperature (10 mV/°C) and Acceleration (500 mV/g) Outputs in One Sensor via a Standard 3 Pin MIL Connection
 - ▶ Popularly sold with SC300 Series Signal Conditioners with built-in Temperature Output

TA234-1A
3 Pin Connector


Connector	Polarity
Pin	
A	(+) Signal/Power
B	(-) Common
C	(+) Temperature Voltage



Stock Product

TA234-2A
CB105 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

TA234-3A
CB218 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TA234		Environmental		
Sensitivity (±10%)	500 mV/g		Operating Temperature Range	-40 to 250°F	-40 to 121°C
Frequency Response (±3dB)	6-480,000 CPM	0,1-80 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	36-180,000 CPM	0,6-30 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 10 g, peak *Vsource ≥ 22V, 12Vbias		Sealing	Welded, Hermetic	
Temperature Measurement Range	-40 to 250°F	-40 to 121°C	Physical		
Temperature Output	10 mV/°C 750 mV = 25 °C (±1)		Sensing Element	PZT Ceramic	
Temperature Sensor			Sensing Structure	Shear Mode	
Electrical			Weight	5.6 oz	160 grams
Settling Time	<2.5 seconds		Case Material	316L Stainless Steel	
Voltage Source (IEPE)	18-30 VDC		Connector (Non-Integral)	3 Pin MIL-C-5015	
Constant Current Excitation	2-10 mA		Resonant Frequency	960,000 CPM	16000 Hz
	14 µA/		Mounting Torque	2 to 5 ft. lbs	2,7 to 6,8 Nm
			Mounting Hardware Supplied	Captive	Captive