

TA253 Series

Low Cost, Low G, Dual Output Sensor, Temperature & Acceleration,
Top Exit 3 Pin Connector, 500 mV/g, 10 mV/°C, ±15%




Product Features

- High Performance in a Low Cost Sensor
- Helps to Detect Bearing Defects and Temperature Changes
- ▶ Temperature (10 mV/°C) and Acceleration (500 mV/g) Outputs in One Sensor via a Standard 3 Pin MIL Connection
 - ▶ Popularly sold with SC300 Series Signal Conditioners with built-in Temperature Output

TA253-1A
3 Pin Connector


Conductor	Polarity
A	(+) Signal/Power
B	(-) Common
C	(+) Temperature Voltage



Stock Product

TA253-2A
CB105 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

TA253-3A
CB218 Amored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metr	Specifications	Standard	Metric
Part Number	TA253	M/ or M8/TA2	Environmental		
Sensitivity (±15%)	500 mV/g		Operating Temperature Range	-40 to 250 °F	-40 to 121 °C
Frequency Response (±3dB)	6-600,000 CPM	0,1-100 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 10 g, peak *Vsource ≥ 22V, 12Vbias		Sealing	Welded, Hermetic	
Temperature Measurement Range	-40 to 250 °F	-40 to °C	Sensing Element	PZT Ceramic	
Temperature Output	10 mV/°C		Sensing Structure	Shear Mode	
Settling Time	5 Seconds		Weight	3.7 oz	104 grams
Voltage Source (IEPE)	18-30 VDC		Case Material	Stainless Steel	
Constant Current Excitation	2-10 mA		Mounting Thread	1/4-28 Blind Tapped Hole	
Spectral Noise @ 10 Hz	1.7 µg/√Hz		Connector (Non-Integral)	3 Pin MIL-C-5015	
Spectral Noise @ 100 Hz	.2 µg/√Hz		Resonant Frequency	960,000 CPM	16000 Hz
Spectral Noise @ 1000 Hz	.12 µg/√Hz		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
	<100				M6x1 or