TC224 Series

Temperature Sensor, Side Exit, °C Output








Product Features

Temperature Sensor

Three Pin MIL Connector

- ▶ Low Cost Temperature Only Sensor
- Temperature Range: -40 to 250 °F (-40 to 121 °C)
- ▶ For Permanent Installation



| Specifications | Standard | | Metric | Specifications | Standard | | Metric |
|---------------------------|----------|----------------------|------------|--------------------------------|------------|-----------|------------|
| Part Number | TC224 | | M/TC124 | <u>Environmental</u> | | | |
| Sensitivity (±10%) | | 10 mV/°C | | Operating Temperature Range | 38 to 250 | | 3 to 121 |
| Frequency Response (±10%) | | | -40 to 250 | operating reinperature italige | °F | | °C |
| | | | °F | Electromagnetic Sensitivity | | CE | |
| Frequency Response (±5%) | 10 mV/°C | | | Sealing | | IP68 | |
| Peak Sensitivity | | -40 to 121 | | <u>Physical</u> | | | |
| | | °C | | Weight | 4.3 oz | | 122 |
| Saturation Time | | .5 Hr | | Weight | 4.0 02 | | grams |
| | | Minimum | | | | 316L | |
| <u>Electrical</u> | | | | Case Material | | Stainless | i |
| Voltage Source (IEPE) | | 4-10 VDC | | | | Steel | |
| Case Isolation | | >10 ⁸ ohm | | Connector (Non-Integral) | | 3 Pin | |
| | | | | | | MIL- | |
| | | | | | | | |
| | | | | Mounting Torque | 2 to 5 ft. | | 2,7 to 6,8 |
| | | | | | lbs. | | Nm |
| | | | | | 1/4-28 | | M6x1 |
| | | | | Mounting Hardware Supplied | Captive | | Captive |
| | | | | | Bolt | | Bolt |