

TR134-M12A Series

RTD Sensor, Side Exit 4 Pin M12 Connector, 500 mV/g, ±10%




Product Features

For use with CTC M4TR Connector & CB123 cabling

- ▶ Base Mounted PT100 RTD Temperature Sensor
- ▶ Temperature and Acceleration in One Sensor
- ▶ 4 Pin M12 Connection

TR134-M12A
4 Pin Connector

Connector Pin	Polarity
1	(+) Signal/Power
2	(-) Common
3	RTD (+)
4	RTD (-)



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TR134-M12A	M/TR134-M12A	<u>Environmental</u>		
Sensitivity (±10%)	500 mV/g		Operating Temperature Range	-40 to 250°F	-40 to 121°C
Frequency Response (±3dB)	6-600,000 CPM	0.1 Hz- kHz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	30-120,000 CPM	0.6 Hz- kHz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 10g, peak *Vsource ≥ 22V, 12Vbias		Sealing	Welded, Hermetic	
Temperature Measurement Range	-40 to 250°F	-40 to 121°C	<u>Physical</u>		
Temperature Sensor	PT100 RTD		Sensing Element	PZT Ceramic	
<u>Electrical</u>			Sensing Structure	Shear Mode	
Settling Time	< 2 Seconds		Weight	3.2 oz	90 grams
Voltage Source (IEPE)	18-30 VDC		Case Material	316L Stainless Steel	
Constant Current Excitation	2-10 mA		Mounting Thread	1/4-28 UNF	
Spectral Noise @ 10 Hz	1.7 µg/√Hz		Connector (Non-Integral)	4 Pin M12	
Spectral Noise @ 100 Hz	0.2 µg/√Hz		Resonant Frequency	1,380,000 CPM	23 kHz
			Mounting Torque	2 to 5 ft-lbs.	2,7 to 6,8 Nm
					M6x1